



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0285	CH'D MATERIAL CALLOUT WAS 1018 IS 1018/1020 CR. CH'D DIMS WAS R.156 IS R.16, WAS .090 IS .09, WAS .188 IS Ø.19, ADDED BLACK OXIDE SPEC, ADDED USED ON TOOLS RBA9928-9, RBA9929-5, RBA9929-9 AND RB600N9929-5, CH'D DWG. TO SHEET METAL TOLERANCE.	10/17/2016	RJC	JAG



#### NOTE:

1. USED WITH RIGGING TOOLS INCLUDING:  
RBA9928-5, RBA9928-9, RBA9928-19,  
RBA9929-5, RBA9929-9 AND RB600N9929-5.

<b>DART AEROSPACE</b>																							
TITLE <b>DRAW BOLT</b>																							
DWG NO. <b>RBA9935</b>	REV <b>2</b>																						
<table border="1"> <tr> <td>MAT'L 1018/1020 CR</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>HEAT TREAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>FINISH BLACK OXIDE</td> <td>.XXX ± .010 FRACTIONS ± 1/8</td> </tr> <tr> <td>SPEC QMSI-6.2.2, B.O. REV D</td> <td>.XX ± .03 ANGLES ± 1°</td> </tr> <tr> <td>DRAWN BY: COLE</td> <td>.X ± .1 SURFACES = 125</td> </tr> <tr> <td>CHECKED: DUERFELDT</td> <td>1. BREAK ALL SHARP EDGES</td> </tr> <tr> <td>OPPS APPR: ANDERSON</td> <td>.015 x 45° OR .015R</td> </tr> <tr> <td>QA APPR: LINDSAY</td> <td>2. DIMENSIONAL LIMITS APPLY</td> </tr> <tr> <td>APPROVED: GILBERT</td> <td>AFTER PLATING</td> </tr> <tr> <td></td> <td>3. INTERPRET DIM AND TOL PER</td> </tr> <tr> <td></td> <td>ASME Y14.5M-2009</td> </tr> </table>		MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED	HEAT TREAT	DIMENSIONS ARE IN INCHES	FINISH BLACK OXIDE	.XXX ± .010 FRACTIONS ± 1/8	SPEC QMSI-6.2.2, B.O. REV D	.XX ± .03 ANGLES ± 1°	DRAWN BY: COLE	.X ± .1 SURFACES = 125	CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES	OPPS APPR: ANDERSON	.015 x 45° OR .015R	QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY	APPROVED: GILBERT	AFTER PLATING		3. INTERPRET DIM AND TOL PER		ASME Y14.5M-2009
MAT'L 1018/1020 CR	UNLESS OTHERWISE SPECIFIED																						
HEAT TREAT	DIMENSIONS ARE IN INCHES																						
FINISH BLACK OXIDE	.XXX ± .010 FRACTIONS ± 1/8																						
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .03 ANGLES ± 1°																						
DRAWN BY: COLE	.X ± .1 SURFACES = 125																						
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES																						
OPPS APPR: ANDERSON	.015 x 45° OR .015R																						
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY																						
APPROVED: GILBERT	AFTER PLATING																						
	3. INTERPRET DIM AND TOL PER																						
	ASME Y14.5M-2009																						
<table border="1"> <tr> <td>SCALE 1:1</td> <td>DATE 8/7/2000</td> <td>SHEET 1 OF 1</td> </tr> </table>		SCALE 1:1	DATE 8/7/2000	SHEET 1 OF 1																			
SCALE 1:1	DATE 8/7/2000	SHEET 1 OF 1																					

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
				1	DRAW BOLT	1018/1020 CR		